

# SUNSHINE CIGS SERIES

## WORLD'S LARGEST CIGS THIN FILM MODULE

Certified according to the standards of IEC61646 and IEC61730  
It offers an excellent power output with high product quality and cost efficiency.

### Electrical Characteristics

\*Standard Test Conditions (STC)

Sunshine CIGS Series	SS1114110K	SS1114120K	SS1114130K	SS1114140K	SS1114150K
Power Output (Pmpp)	<b>110Wp</b>	<b>120Wp</b>	<b>130Wp</b>	<b>140Wp</b>	<b>150Wp</b>
Max. Power Voltage (Vmpp)	56.5V	57.69V	59.87V	64V	66.4V
Max. Power Current (Impp)	1.94A	2.13A	2.17A	2.2A	2.25A
Open Circuit Voltage (Voc)	85.6V	85.25V	87.33V	90.63V	92.07V
Short Circuit Current (Isc)	2.41A	2.62A	2.62A	2.59A	2.59A
Max. System Voltage	1000V	1000V	1000V	1000V	1000V
Power Tolerance	+/-5%				
Maximum System Voltage	1000Vdc (IEC), 600 Vdc (UL)				
Operating Temperature	-40°C to 85°C				



### Limited Warranty

#### Product Guarantee

Warranty of the Materials and the Workmanship for 2 years.

#### Power Guarantee

90% of the minimal rated Power Output for 10 years after shipment.  
80% of the minimal rated Power Output for 20 years after shipment.

### Mechanical Characteristics

Size	1100mm x 1400mm
Depth	7.7mm
Weight (w/back rail, w/o back rail)	33kg / 28.5kg
Type of Frame	w/back rail, w/o back rail
Front Cover	Tempered glass
Back Cover	Float glass
Encapsulation	Glass / EVA / Glass
Snow/Wind Load (IEC)	2400Pa (w/o back rail), 5400Pa (w/ back rail)
Junction box, Connector	IP 68, MC-4 compatible
Output Cable	14 AWG ( 2.5mm <sup>2</sup> )
Cell Type	162 CIGS Cells
Safety Class	II
Fire Rating	Class C



ISO  
9001:2008




Safety Class II



# SUNSHINE

## Physical Specification



## IV Curve

